
Line L: Fasteners



<u>Across</u>

- 4. type of end produced by tubing cutters
- 6. fabric covers protect hoses against
- 7. a fastener that has threads on both ends or full length
- 8. adhesive used for tub surrounds and tiles
- **11.** indicated by metric numbers stamped into the head of a bolt (2 words)
- 18. adhesive used to fill gaps
- 19. a pin that prevents damage to machinery from overloading
- 21. locking groove cut into a gear shaft
- 22. systems that use JIC fittings
- 23. thread compound is used to prevent this

- 25. hollow pin, split lengthways
- 27. diameter of threads from root to
- 28. thread compound is used to prevent this
- 29. Heli-coil is a trade name for thread
- 30. adhesives with little or no moisture resistance (2 words)
- 31. identifiers on high pressure hose fittings

<u>Down</u>

- ____: term referring to wall 1. pipe thickness
- 2. a fastener that threads into a tapped hole (2 words)
- 3. three types of tap: plug, bottoming
- 5. The U in UNF or UNC thread series

- _: term refering to thread _ inches per thread
- **10.** thread _ _: tool used to repair damaged external threads
- 12. angle, in degrees, between NPT thread flanks
- flare makes the tube end **13.** a
- stronger and prevents splitting **14.** a fastener that does use a nut
- **15.** pin used for aligning material 16. urea resin is a type of _
- adhesive 17. fitting used to reduce pipe size on
- same plane
- 20. term for removing first layer of a hose
- **24.** hose fittings are classified as ___ or permanent
- 26. acronym for dry-seal threads